

### 230 K Bearing Series

Bearing Size	Shaft Dia. (d1)in.	Designations				Mass lbs.	Dimensions			
		Complete Adapter	Lock-nut	Lock-washer	Sleeve		L	F	(d2)Pitch Diameter	Threads Per Inch
23024 K	4 3/16	SNW 3024	N 024	W 024	S 3024	4.61	2.947	1.250	4.660	12
23026 K	4 7/16	SNW 3026	N 026	W 026	S 3026	6.79	3.237	1.313	5.050	12
23028 K	4 15/16	SNW 3028	N 028	W 028	S 3028	6.65	3.340	1.375	5.441	12
23030 K	5 3/16	SNW 3030	N 030	W 030	S 3030	7.22	3.492	1.406	5.832	12
23032 K	5 7/16	SNW 3032	N 032	W 032	S 3032	10.58	3.711	1.468	6.200	8
23034 K	5 15/16	SNW 3034	N 034	W 034	S 3034	11.92	4.019	1.500	6.575	8
23036 K	6 7/16	SNW 3036	N 036	W 036	S 3036	12.73	4.337	1.531	6.982	8
23038 K	6 15/16	SNW 3038	N 038	W 038	S 3038	12.25	4.412	1.594	7.388	8
23040 K	7 3/16	SNW 3040	N 040	W 040	S 3040	17.20	4.750	1.656	7.763	8
23044 K	7 15/16	SNW 3044	N 044	W 044	S 3044	20.47	5.130	1.750	8.544	8

